

# Wavecom



# SEW VOT-52

## *Voltage & Continuity Tester*

**South Australia**  
257 Grange Road  
Findon, SA 5023  
P: +61 08 8243 3500  
F: +61 08 8243 3501  
E: sales@wavecom.com.au

**Victoria**  
Suite 8, 79-83 High Street,  
Kew, VIC 3101  
P: +61 03 9897 4711  
F: +61 08 8243 3501  
E: sales@wavecom.com.au

**Western Australia**  
Unit 2/17 Casino Street,  
Welshpool, WA 6016  
P: +61 08 9353 1943  
F: +61 08 9353 4319  
E: saleswa@wavecom.com.au





# SEW VOT-52

## Voltage & Continuity Tester

### Features

- ◇ Voltage test: 12V to 1000V AC/DC (8 LEDs) with indication by buzzer.
- ◇ Voltage range: 12V, 24V, 50V, 120V, 230V, 400V, 750V, 1000V
- ◇ Test leads positioned at 19mm apart
- ◇ Interchangeable probe tip for 2mm and 4mm
- ◇ Polarity test : LED +/-
- ◇ Audible continuity test
- ◇ Phase rotation test
- ◇ ELCB / RCD trip test
- ◇ Self-test button to ensure proper function of the device prior to testing
- ◇ IP65 Rated Waterproof Design
- ◇ Phase / Neutral identification
- ◇ Rubberized double-molded housing
- ◇ Flashlight function
- ◇ Safety standards: IEC/EN 61010-1 CAT III 1000V IEC/EN 61010-1 CAT IV 600V IEC/EN 61243-3 EN 61326-1

### Diagram



**South Australia**  
257 Grange Road  
Findon, SA 5023  
P: +61 08 8243 3500  
F: +61 08 8243 3501  
E: sales@wavecom.com.au

**Victoria**  
Suite 8, 79-83 High Street,  
Kew, VIC 3101  
P: +61 03 9897 4711  
F: +61 08 8243 3501  
E: sales@wavecom.com.au

**Western Australia**  
Unit 2/17 Casino Street,  
Welshpool, WA 6016  
P: +61 08 9353 1943  
F: +61 08 9353 4319  
E: saleswa@wavecom.com.au

# SEW VOT-52

## Voltage & Continuity Tester



### Specifications

Voltage Test	12V to 1000V AC/DC
Voltage Range	12V, 24V, 50V, 120V, 230V, 400V, 750V & 1000V
Working Frequency	40-65Hz
Voltage Protection	1100V AC/DC
Continuity Range	<200k OHMS
Phase Rotation Test Range	100V~1000V measure between two phases, instrument in hand
Operating Temperature & Humidity	0DEGC to 40DEGC - Maximum 80% R.H.
Probe Distance	19mm apart
Power Source	2x 1.5V AAA Batteries
Dimensions & Weight	248mm x 68mm x 34mm - 215g
Safety Standards	IEC/EN 61010-1 CAT III 1000V IEC/EN 61010-1 CAT IV 600V IEC/EN 61243-3 EN 61326-1
Accessories	Instruction Manual & Batteries

### Ordering Information

◇ SEW VOT-52 Voltage & Continuity Tester

WCM-VOT-52

South Australia  
257 Grange Road  
Findon, SA 5023  
P: +61 08 8243 3500  
F: +61 08 8243 3501  
E: sales@wavecom.com.au

Victoria  
Suite 8, 79-83 High Street,  
Kew, VIC 3101  
P: +61 03 9897 4711  
F: +61 08 8243 3501  
E: sales@wavecom.com.au

Western Australia  
Unit 2/17 Casino Street,  
Welshpool, WA 6016  
P: +61 08 9353 1943  
F: +61 08 9353 4319  
E: saleswa@wavecom.com.au

